



## Product Description

Type CI hydro-lock sleeve is for interchangeable tool assembly. Used for assembly of cutterheads and saw blades on moulders, rip saws, and tenoners. The design allows mounting of multiple tools and quick switch between tools.

Max. Speed: 9000 rpm.

## Highlight Features

1. Easy and quick pressurization with an Allen T wrench;
2. We offer a comprehensive range of products to match most grips in the market;
3. With accessories, multiple tools can be mounted and operated simultaneously.

## Product Specifications

SKU	Product	D	D1	D2	D4	D5	D6	D7	D8	L	L1	H	N	K
G012 03003	CI 1-1/2"/50 x 85	1-1/2"	50	102	64	14	9.5	65	15	85	65	8.5	8	10
G012 03006	CI 1-13/16"/60 x 75	1-13/16"	60	102	74	14	9.5	75	15	75	55	8.5	8	10
G012 03010	CI 1-13/16"/65 x 85	1-13/16"	65	108	80	14	9.5	80	15	85	65	8.5	8	10
G012 03511	CI 40/50 x 75	40	50	102	64	14	9.5	65	15	75	55	8.5	8	10
G012 03516	CI 40/60 x 75	40	60	102	74	14	9.5	75	15	75	55	8.5	8	10
G012 03517	CI 40/60 x 95	40	60	108	74	14	9.5	75	15	95	75	8.5	8	10
G012 03518	CI 40/60 x 115	40	60	108	74	14	9.5	75	15	115	95	8.5	8	10
G012 03530	CI 50/60 x 75	50	60	102	74	14	9.5	75	15	75	55	8.5	8	10
G012 03531	CI 50/60 x 95	50	60	108	74	14	9.5	75	15	95	75	8.5	8	10
G012 03532	CI 50/60 x 115	50	60	108	74	14	9.5	75	15	115	95	8.5	8	10

Please note that except for the dimensions marked in imperial, all the other dimensions in the above table are in metric (mm).